



POLIMASTER®



Innovating Radiation Detection Technologies Since 1992

CONTINUOUS AND PULSE X-RAY AND GAMMA RADIATION PERSONAL DOSIMETER

PMT610B PM1610B-01



These electronic personal dosimeters are excellent instruments for personnel, exposed to pulsed X-ray and gamma radiation.

The instruments provide measurement of dose equivalent and dose equivalent rate of continuous and pulsed X-ray and gamma radiation, as well as time of dose accumulation.

Devices have audible, visual and vibration alarms to warn the user when preset dose/dose rate threshold levels are exceeded.

For reading data from dosimeters the special software Personal Dose Tracker is provided. It allows to record and monitor radiation exposure of users of dosimeters.

The device is ready for use immediately after installing the battery.

PM1610B-01 version can be used with different types of wireless readers in compliance with ISO 15693.



Features

- Easy to use
- Measurement of pulse X-ray and gamma radiation with pulse duration 1 ms and up
- Dose rate measurement up to 10 Sv/h (1000°rem/h) and dose measurement up to 20°Sv (2000 rem)
- Two independent alarm thresholds for dose and dose rate
- Default settings for dose: threshold 1 – 5 mSv (500 mrem), threshold 2 – 10 mSv (1000 mrem)
- Audible, visual and vibration alarms
- Wide energy range from 20 keV to 10 MeV
- Settings can be controlled (blocked by the user to change) from a PC via USB
- Ability to display measurements in Sv or rem
- Turning off the alarm by pressing any button
- Shockproof hermetic case
- Light weight and small dimensions

Applications

- First responders
- Customs and border patrol
- Medical professionals
- Radiological and Radionuclide isotope laboratories
- Professionals exposed to pulse radiation

ALARM

PULSE RADIATION

MEASUREMENT



www.polimaster.com

www.polimaster.us

www.polimaster.eu

www.polimaster.jp



CONTINUOUS AND PULSE X-RAY AND GAMMA RADIATION PERSONAL DOSIMETER

PM1610B PM1610B-01



SPECIFICATIONS

Detector	Geiger-Mueller tube
Dose equivalent rate (DER) indication range	0.01 μSv/h - 12.0 Sv/h (1 μrem/h - 1200 rem/h)
DER measurement range	0.1 μSv/h - 10.0 Sv/h (10 μrem/h - 1000 rem/h)
DER threshold range (in all measurement range)	Two threshold levels
Dose equivalent (DE) indication range	0.001 μSv - 24.0 Sv (0.1 μrem - 2400 rem)
DE measurement range: - continuous photon radiation (current) - pulsed photon radiation (pulse duration not less than 1 ms)	0.05 μSv - 20.0 Sv (5 μrem - 2000 rem) 10 μSv - 20.0 Sv (1000 μrem - 2000 rem)
DE threshold range (in all measurement range)	Two threshold levels Default settings for dose: - threshold 1: 5 mSv (500 mrem), - threshold 2: 10 mSv (1000 mrem)
Minimum pulse duration of X-ray and gamma radiation	1 ms at multiple exposure (more than 10 pulses) 10 ms at single exposure
Accuracy of DER measurement	$\pm(10 + 0.0015/\dot{H} + 0.0015\dot{H}) \%$, where H - DER value in mSv/h
Accuracy of DE measurement in the range 0.05 μSv - 20.0 Sv	$\pm 20\%$
Energy range	20 keV - 10 MeV
Energy response relative to 0.662 MeV (¹³⁷Cs) in the DER and DE measurement mode, not more than	- 60% 20 keV - 33 keV; - 40% 33 keV - 48 keV; $\pm 30\%$ 48 keV - 3 MeV; $\pm 50\%$ 3 MeV - 10 MeV.
Communications	- USB interface - ISO15693 interface for PM1610B-01
Features	- PC communication via USB - Audio, visual and vibration alarms - Holder with clip
Automatic data logging	7500 data points
Power supply	Battery type LR03/AAA
Operating time on new battery in normal conditions	no less than 20 days
Low battery (partial and critical)	Indication on LCD
Operating conditions: - temperature range - pressure	-20 - +50°C 84 - 106.7 kPa
Case Protection Class	IP65
Dimensions	71x59x20 mm
Weight	90 g

Designed to meet ANSI N42.20-2006 and IEC 61526:2010 requirements

Design and specifications of the device can be changed without further notice.



North and South America

Polimaster Inc.
44873 Falcon Place, Suite 128
Sterling, VA 20166, USA
Phone: +1 703 525 5075
Fax: +1 703 525 5079
info@polimaster.us

www.polimaster.us

Europe

Polimaster Europe UAB
Ezero Str. 4, LT-13264 Didziasalis,
Vilnius region, Republic of Lithuania
Phone: +370 5 210 2323
Fax: +370 5 210 2322
polimaster@polimaster.lt

www.polimaster.eu

Asia, Africa, Australia and Oceania

Polimaster Ltd.
51, Skoriny St., Minsk
220141, Republic of Belarus
Phone: +375 17 396 3675
+375 17 268 6819
Fax: +375 17 264 2356
polimaster@polimaster.com
www.polimaster.com

Japan

Polimaster Japan K.K.
AUBE2 5-177 Kuratsuki
Kanazawa, Ishikawa Prefecture
920-8203 Japan
Phone: + 81 076 201 8623
Fax: + 81 076 201 8624
pacific@polimaster.jp
www.polimaster.jp